

SPECIFICATIONS

А

RAILS, POSTS: 6061 TG ALUMINUM ALLOY 1 1/4" I.D. SCH 40

GATE: 1 1/4" TUBULAR ALUMINUM SELF CLOSING WITH COIL SPRING, ZINC PLATED

COUNTERFLASH MOUNTING BRACKETS: 3/16" ZINC PLATED STEEL FASTENED TO STEEL BACKING PLATE

FITS HATCH SIZES UP TO 30" X 96"

CERTIFICATIONS: MEETS OSHA 29 CFR 1910.23 GUARDING FOR OPENINGS REQUIREMENTS; SUPPORTS 200 LBS. FORCE

FINISH: SAFETY YELLOW POWDER COAT

	FASTENED TO STEEL BACKING PLATE									
E	BOLTS: HEX HEAD BOLTS 3/8"-16 x 3/4" GRADE 5 ZINC PLATED									
	RAILING FITTINGS AND PLUGS: MANUFACTURER'S STANDARD CAST									
	WITH SET SCREW HOI	LD					NAME	DATE		
						DRAWN	SJB	TODAY		
PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.										
	8	7	6	5	4	3				

2		1		
Description	n Line 1	(ΩΤΥ.	
RAIL, 1-1/4"	X 37.75L,		2	
RAIL, 1-1/4"	X 50.50L,		2	
RAIL, 1-1/4"	X 51.75L,		2	
PKG, CORNER	POST, ZPS		4	
PKG, SIDE PC	OST, GALV		1	
FTG, EL	BOW,		2	D
FTG, T	ΈE,		2	
FTG, CROSS	S ELBOW,		1	
FTG, DBI	L TEE,		1	
FTG, ENI	D CAP		1	
GATE,	30,		1	



С

В