

WATER



240
P/N 00100

MODEL 240 utilizes the cooling, soaking, and penetrating effect of a 45- to 55-foot stream of **WATER**. The 55-second discharge time makes it very effective for inexperienced operators for use on Class A fires that include combustibles such as wood, cloth, paper, and many plastics. This extinguisher is constructed with a chrome-plated brass valve and polished stainless steel cylinder, which helps eliminate corrosion.

EXTINGUISHER
SHIPS EMPTY



RUGGED

- 5-Year manufacturer's warranty
- Stored-pressure design
- Polished stainless steel cylinders
- All-metal valve construction
- Exclusive crevice-free, butt-welded cylinder
- Temperature range 40°F to 120°F

USER-FRIENDLY

- Maximum visibility during discharge
- Large loop stainless steel pull pin
- QR coded and multilingual labels

OPTION

- Model 506B anti-freeze charge (Temperature range -40°F to 120°F)

MANUFACTURED AND TESTED TO UL STANDARDS
COMPLIES WITH NFPA 10 STANDARD
ISO-9001/ISO-14001 CERTIFIED
UL LISTED

CONFORMS TO TEST STANDARDS:
CAN/ULC-S507 - UL 626 &
CAN/ULC-S508 - UL 711

THE MODEL 240 MAY BE FREEZE-PROTECTED TO -40°F
BY ADDING A MODEL 506B CHARGE

AGENT TYPE	WATER
DESIGN	Hose & Nozzle
MODEL NUMBER	240
UL & ULC RATING	2A
CAPACITY	2.5 Gal
*SHIPPING WT. (LBS)	7.5
HEIGHT (IN.)	24.5
WIDTH (IN.)	9
DEPTH (IN.)	7
RANGE (INITIAL-FT)	45-55
DISCHARGE TIME (SEC.)	55
NOMINAL OPERATING PRESSURE	100 PSIG
INCLUDED BRACKET	Wall

*Shipping weight includes box.

