

# 4200R Series

# Commercial Wide Stile Rim Exit Device

## Architectural Submittal Sheet



**RIM**  
ANSI TYPE 1



ADA COMPLIANT

### Specifications

<b>CHASSIS:</b>	• Corrosion resistant plated steel
<b>RAIL:</b>	• Heavy gauge steel or stainless steel
<b>LATCH:</b>	• RIM (R) – 3/4" throw
<b>BACKSET:</b>	• 2-3/4" Backset Compatible with 161 prep
<b>HAND:</b>	• Device is non-handed
<b>DOGGING:</b>	• Hex key dogging standard • Dogging not available on fire listed devices
<b>MINIMUM STILE WIDTH:</b>	• 4-1/4" for device (exit only) • Minimum stile requirements with trim varies by trim type
<b>DOOR THICKNESS:</b>	• 1-3/4" standard
<b>DOOR WIDTH:</b>	• Standard for 3 ft doors, option available for doors up to 4'
<b>FINISHES:</b>	• 605 – Polished Brass, 626 – Satin Chrome, 630 – Satin Stainless Steel, 689 – Aluminum, 695 (N/A)- Duro Bronze, 696 – Gold • Optional Anti Microbial Coating available on 626 and 630 finishes only
<b>FASTENERS:</b>	• Includes machine screws and wood screws • Sex nuts supplied with all Fire Listed devices
<b>WARRANTY:</b>	• Five (5) year limited warranty
<b>CERTIFICATIONS, LISTINGS, COMPLIANCES:</b>	• UL 305 listed for "Panic" , UL listed for "Fire Exit Hardware" labeled for up to 1-1/2 hours, 3'0" x 7'0" Max Size • Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings • TAA compliant. Country of origin: Taiwan